

CHAINMAX WR 68

Product code: 261800801

Adherent, water repellent chain oil

This product is a very adherent and are resistant to high pressure. It is particularly suitable as water resistant agent and lubricant of drive chains and overhead conveyor chains. Chainmax WR fluids do not splash or drop and will therefore ensure a better lubrication compared to conventional lubricants.

It can be used at service temperatures from -20 up to 150 °C. Thanks to its superior anticorrosive capacity the product will perform very well at sea and in other corrosive ambiances. A truly multipurpose oil for hoist chains, forklift trucks, chain saws, general machinery, delicate moving parts of robots and whenever a premium light grade oil is required.

To obtain maximum results, apply the product to dry and clean surfaces.

Benefits & Advantages

- Non-drip properties will extend the lubrication intervals and ensure a clean working area
- Excellent penetration properties provide protection of the moving chain pins and bushes
- Excellent corrosion resistance and dewatering properties allow application to wet or recently washed chains
- The EP additive provides a high degree of wear protection and extends chain life

Typical Performance Data

Typical	Value
Appearance	Clear fluid, oily liquid
Viscosity @ 40 °C, cSt	68
Viscosity Index	>90
Flash point, °C	>200
Pour point, °C	-10
Copper corrosion, 3hrs /100 °C	1a

All performance data on this Technical Data Sheet are indicative only and can vary during production.