

COOLMAX CFC 32

Product code: 262200101

Compressor lubricant for CFC refrigeration systems

This product is formulated for use in refrigeration systems that use chlorinated fluorocarbon refrigerants. It is a highly refined naphthenic oil with excellent low temperature properties and a very low wax content to avoid flocculation problems in service.

Application

Recommended for general purpose lubrication of refrigerator compressors working with CFC (chlorinated fluoro-carbon) refrigerants such as R11 and R12. It may also be used for HCFC (hydro chlorinated fluorocarbon) refrigerants such as R22, R123, R-124, R-141b, R142b, R-502 and Methyl Chloride, Carbon Dioxide (R-744) and Ammonia (R-717) at moderate temperatures. The product is not suitable for use with HFC refrigerants such as R134a or R23.

Benefits & Advantages

- Greater chemical resistance against reactions with the refrigerant
- Better fluidity at lower temperatures which warrant a better efficiency and avoids blockage of pipes and coolers.
- Good dispersibility for optimal heat transfer and oil return

Gas type suitability

The product is suitable for processing the following gases:

R11	R12	R502	R22	R123
R414b	R142b	R124	R401a	R409a
R290	R600/600a	R502	R717	R744

COOLMAX CFC 32

Product code: 262200101

Typical Performance Data

Typical	Test Method	Value
Appearance	-	Bright and clear
Colour	ASTM D1500	1
Specific gravity @ 15 °C	-	0.910
Viscosity @ 40 °C, cSt	ASTM D445	30
Viscosity @ 100 °C, cSt	ASTM D445	4.4
Pour point, °C	ASTM D97	-40
Flash point COC, °C	ASTM D92	168
Copper corrosion, 24 hrs / 150 °C	ASTM D130	1b
Dielectric strength, kV	IEC 156	45
Dissipation factor @ 25 °C 2 mm	IEC	0.01
Water content, ppm max.	ASTM D1533	50
Freon 12 insoluble, wt. % max.	DIN 51590	0.05

All performance data on this Technical Data Sheet are indicative only and can vary during production.