

FOODMAX GEAR PAG 150

Product code: 263500901

Synthetic gear and chain oil for the food industry

This product is a range of high-performance long life synthetic food grade gear oils particularly suited for the lubrication of drive chains, conveyor chains, gearboxes and reduction units. The fluids are provided with excellent anti wear properties, high stability to oxidation and a low pour point. Will resist mechanic shearing, very stable to ageing and present a very good viscosity - temperature behavior. These fluids are adhesive and will therefore prevent from wear during start-up operation.

This product is NSF H1 registered for incidental food contact.

Benefits & Advantages

- Extremely good oxidation stability extending lubricant life
- Excellent water-resistant properties, demulsibility ensures total separation of water from oil
- Adhesive
- Penetrates to chain links and pins reducing wear and extending chain life
- Non-dripping
- Protects from corrosion even in presence of alkali materials
- Extremely wide temperature range
- Excellent resistance to high loads
- Less friction, resulting in lower oil temperatures
- Lower energy consumption resulting in a lower carbon footprint

Applications

This product is intended for the lubrication of gearboxes, worm gears, endless screws, circulating systems, bearings and conveyor chains (up to 240 °C).

This product suits very well in very wet environments as it remains unaffected by water.

Cautions

The product is neither miscible with mineral base oils nor with different nature synthetic oils. So it is advisable to proceed to a good cleaning (flushing) of the mechanism to be lubricated prior to use the oil.

Performance level

- FZG gear test (DIN 51354) A/8.3/90: > 12
- FAG FE 8 roller bearing test weight loss roller (mg): 12
- Vickers vane pump test V 104-c-10 (DIN 51389 part 2): 2
- Brugger-Weingarten max load (N/mm²): 47
- Busak & Shamban micro scratching test: pass
- DIN 51517-3
- David Brown Type G

FOODMAX GEAR PAG 150

Product code: 263500901

Typical Performance Data



Property	Unit	Test Method	Value
Colour	-	Visual	Colorless
Density @ 20 °C	g/cm ³	ASTM D1298	0.998
Viscosity @ 40 °C	mm ² /s	ASTM D445	162
Viscosity @ 100 °C	mm ² /s	ASTM D445	27
Viscosity Index	-	ASTM D2270	202
Flash point	°C	ASTM D92	278
Pour point	°C	ASTM D97	-39
TAN (max)	mgKOH/g	ISO 6618	1.6
Copper Corrosion	-	ASTM D130	1a
4-ball Wear, 1200 rpm, 75°C, 40kg	-	ASTM D4172	0.35
4-ball Weld load, kg	kg	ASTM D-2783	160
Rust Test	-	-	Pass
FZG load stage	-	DIN 51354	>12
NSF approval	H1	-	Pending
Kosher approval	-	-	YES
Halal approval	-	-	YES

All performance data on this Technical Data Sheet are indicative only and can vary during production.