

GREASE BARIUM COMPLEX L 2 S

Product code: 264900301

Low temperature and high speed synthetic grease

This product is a complex soap thickened synthetic grease. It provides high resistance to oxidation, superior anticorrosive capacity, E.P. characteristics, good adherence to metal and good resistance to water, and resistance to vapour, acid and alkaline solutions.

This product is specially designed for bearings which operate in a wet environment. It is also specially designed for spindles, cams, joints and turbines. Extremely suitable for the lubrication of spindles in CNC machines. These products are recommended for their performance in combination with metalworking emulsions.

Benefits & Advantages

- Excellent behaviour to temperatures
- Corrosion protection
- Long life grease
- Extended bearing life
- Lower grease consumption
- Extends lubrication intervals
- Good pumpability
- Excellent adhesiveness

Typical Performance Data

Property	Test Method	Value
Colour	-	Ivory
Thickener, soap type	-	Barium complex
Base oil nature	-	Synthetic
Base oil viscosity @ 40 °C, cSt	-	22
Base oil viscosity @ 100 °C, cSt	-	5
NLGI class	DIN-51818	2
Penetration @ 25 °C, x 0,1 mm	ASTM D217	265-295
Drop point, °C	ASTM D566	>220
Oil separation 7 days/40 °C, %	IP-121	3
Flow pressure @ -40 °C, mbar	DIN-51805	4
4-balls, Welding load, kg	IP-239	320
4-balls, Wear scar diameter 1 1/4 kg, mm		0.50
EMCOR corrosion test	DIN-51802	0
Copper corrosion 24hrs/100 °C	ASTM D4048	1b
Resistance to water wash-out, 80 °C, %	ASTM D1264	1.50
Evaporation loss, weight %, 22hrs/100 °C, %	ASTM D972	<0.80
SKF-ROF test, 20.000 rpm, 110 °C	-	L50 = 1910
Service temperatures, °C	-	-50 – 150
Speed factor	-	10 ⁶

All performance data on this Technical Data Sheet are indicative only and can vary during production.