

HYDROMAX HT ECO 22

Product code: 266101501

Hydro treated based high performance readily biodegradable hydraulic fluid

This product is a high performance hydraulic and hydro turbine fluid, based on the latest technology hydro treated base oil and ash less (zinc free) additive technology. The use of special additive packs warrants optimal performance and a long service life. It combines high viscosity – temperature characteristics with good extreme pressure and anti-wear properties for reliable and trouble-free performance even at high operating temperatures. The long lifetime of this product (up to 5 times longer than standard mineral Hydraulic oils) makes this product not only Biodegradable and non-toxic but very sustainable. The long life and cleanliness results in less waste material, low oil filter consumption and as a result of very low friction a proven lower energy consumption (between 3 and 5%) can be generated. It has very good water separation properties which allow draining of water from systems when water intrusion is seen. Conductivity for this product is very low which allows this oil to work as a Transformer and Hydraulic oil at the same time.

Applications

- Particularly suitable for hydraulic equipment & hydro turbines which are environmentally sensitive
- Can be used in all available hydraulic applications, as well as light gear boxes and is perfectly suitable for general lubrication purposes
- Suitable for ROV units
- Developed to provide trouble free operation, especially in cases where a conventional based hydraulic fluid fails (sludge and deposit creation at higher temperatures etc.)
- Recommended for high pressure hydraulic systems or equipment operating over wide temperature ranges where it is critical to retain viscosity-temperature characteristics under high shear conditions
- The high viscosity index of this product ensures a low start up viscosity, as also a stable protecting lubricating film at high operating temperatures
- Formulated to meet and exceed; Denison HF-0, Eaton Vickers M-2950-S and I-286-S

Benefits & Advantages

- Excellent anti-wear protection
- Good emulsifying and air-release properties
- Good anti-oxidation for a long service life (up to 10.000 hours, ASTM D943)
- Lasts up to five times longer than the leading conventional hydraulic fluids
- Excellent anti-corrosion properties
- Excellent low & high temperature properties
- No sludge and deposit creation due to the absence of aromatics
- Zinc free formulation
- Low friction and therefore up to 5% less energy consumption in comparison with conventional hydraulic fluids

HYDROMAX HT ECO 22

Product code: 266101501

Typical Performance Data

Property	Test Method	Value
Appearance	Visual	Bright & clear
Density @ 29,5 °C, kg/dm ³	ASTM D1298	0.860
Viscosity @ 40 °C, mm ² /s (cSt)	ASTM D445	22
Viscosity @ 100 °C, mm ² /s (cSt)	ASTM D445	5
Viscosity Index	ASTM D2270	150
Flash point, °C	ASTM D92	220
Pour point, °C	ASTM D97	-35
Copper corrosion test @ 100 °C / 3 hrs.	ASTM D130	1a
Corrosion prevention test A (distilled water) test B (sea water)	ASTM D665	Pass Pass
Emulsion characteristics	ASTM D1401	40/40/0 (15)
T.A.N., mg KOH/g, max	ASTM D664	-
FZG	DIN 51354	-
Oxidation Resistance	ASTM D943	>10000
Foaming characteristics, 10 min <ul style="list-style-type: none"> • Sequence I • Sequence II • Sequence III 	ASTM D892	Nil Nil Nil

All performance data on this Technical Data Sheet are indicative only and can vary during production.