

INOMAX H 5

Product code: 264908101

Multipurpose lubricant for severe circumstances

An aluminium complex soap thickened, soft, bitumen free, grease incorporating solid lubricants, extreme pressure additives, and a blend of antioxidants and corrosion inhibitors, combined to provide highly effective lubrication with excellent corrosion protection.

The adhesive nature of this product makes it suitable for a wide range of applications in very wet and aggressive environments. Suitable for the lubrication of sliding surfaces, open gears, heavy-duty bearings subjected to really aggressive working conditions. The de-watering properties of this product make it highly suitable for application to wet slides and surfaces.

Benefits & Advantages

- Easy to apply in all weathers
- Dewaterers and can be applied to wet surfaces
- Very resistant to water wash off extending re-lubrication intervals
- Excellent load carrying properties extending component life
- Versatility enables one product to used for multiple applications
- Suitable for pumping through centralized lubrication systems
- Contains micronized graphite

Typical Performance Data

Typical	Test Method	Value
Appearance		Black adhesive grease
Thickener		Aluminium complex
Base oil type		Solvent refined mineral oil
Base oil viscosity @ 40 °C, cSt		300
NLGI class		0/1
Worked penetration	IP50	320-350
Solids		Graphite
Solids content, %		5
Timken OK load	IP326	20
4 ball wear test, welding load, kg	IP239	700
Water spray off, loss %	ASTM D404	<0,5
Operating temperatures, °C		-30 – 150

All performance data on this Technical Data Sheet are indicative only and can vary during production.