

# PASTE ANTI SEIZE

Product code: 265000401

## Anti-seize and anti-corrosive paste

Specially designed for very high temp operations wherever there is corrosion, seizing, flaying and generally seizing of threaded joints.

## Applications

- Protects from flaying, corrosion, seizing
- Makes the assembling and disassembling operation easier
- Allows to recover and re-use of the parts, which eventually saves money for replacement parts
- Resists high load thanks to the high solid lubricants content
- Long life and high efficiency
- Resists temperature up to 1100 °C (without contact with air)

## Performance level

It meets FORD SAM-1C 9107-A.

## Typical Performance Data

Typical	Test Method	Value
Colour		Dark copper
Thickener, soap type		Bentonite
Base oil nature		Mineral
Base oil viscosity @ 40 °C, cSt		100
Density @ 25 °C, gr/cm <sup>3</sup>		1.10-1.20
NLGI consistency	DIN 51818	2
Penetration @ 25 °C, x 0,1 mm	ASTM D217	265-295
Solids type		Copper
Solids content, %		35-40
Dropping point, °C	ASTM D566	>300
Steel strip corrosion 24hr/100 °C	ASTM D4048	Nil
Aluminium strip corrosion, 24hr/100 °C	ASTM D4048	Nil
Copper strip corrosion, 24hr/100 °C	ASTM D4048	1b
4 balls test welding load, kg	IP-239	300
Water resistance 3hrs/90 °C	DIN 5807	1
Operating temperatures, °C		-15 – 140
Application temperature (dry film), °C		1100

All performance data on this Technical Data Sheet are indicative only and can vary during production.