

Performance[®] ALU-ZINC SPRAY #53

BRIGHT COLORED ZINC PROTECTION COATING SPRAY

Product Code
267800301

Industrial Spraycans



PAINT

Bright Colored Zinc Protection Coating Spray

This product is a high quality Alu-Zinc spray to treat galvanized and untreated steel. Performance Alu-Zinc Spray is used as a rust and corrosion protection on iron and steel surfaces.

Performance Alu-Zinc spray can be used for repair of damaged galvanic surfaces, protection of exhaust systems and protection of welding seams.

Benefits:

- Resistant to petrol, chemicals and weather influences
- Outstanding cathodic corrosion prevention
- Excellent adhesion
- Good filling properties
- Lighter color because of the aluminum component in this formula
- Spot-weldable
- Resists temperatures up to 250°C



e 400ml

Typical Performance Data

Typical	Value
Base	Epoxy-Ester
Colour	Silver-Grey
VOC, % w/w	76
Solid content, % w/w	24
Coverage, m ₂	1.25 to 1.75
Dust dry	10 to 15 min
Tack free	20 to 30 min
Hardened/Re-sprayable	>24h
Heat resistant	Up to 250°C

How to use:

The surface should be clean, dry and free of grease and oil. The aerosol should have room temperature. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter. Apply the Alu-Zinc spray in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

All performance data on this Technical Data Sheet are indicative only and can vary during production.