

# SLIDEMAX 68

**Product code:** 261400301

## Slide or guide way lubricant

These products are specially compounded oils developed for the lubrication for slides and ways. They are specially developed to eliminate the phenomenon of stick-slip in machine tool operation. The combination of compounding, special base oils and additives gives this product outstanding stability, extreme oiliness, adhesiveness and exceptional load carrying ability.

## Applications

Way guides and slide ways it can be used for horizontal applications.

## Benefits & Advantages:

- Excellent metal wetting properties
- Non corrosive to both metal and non-metal materials
- Exceptional load carrying capabilities
- Eliminates stick slip
- Provides excellent demulsibility characteristics in the present of water based cutting fluids
- No adverse reaction to resin coated surfaces
- Very good corrosion protection

## Approvals

- ISO 6743-4: HG
- ISO 6743-13 GA
- Cincinnatti Milacron P-47 (ISO VG 68)
- Cincinnatti Milacron P-50 (ISO VG 220)
- Cincinnatti Milacron P-53 (ISO VG 32)
- Cincinnati Milacron P-69
- DIN 51524 part 2 HLP
- DIN 51517 part 3 CLP

## Typical Performance Data

Typical	Value
Density @ 25°C, g/ml	0.88
Viscosity @ 40 °C, cSt	68
Viscosity Index	>90
Flash point, °C	>200
Pour point, °C	<-10
Cu corrosion	1a

All performance data on this Technical Data Sheet are indicative only and can vary during production.