

VACUMAX 220

Product code: 261700701

Mineral oil based vacuum pump fluid

Advanced vacuum pump fluid specifically designed for use in mechanically operated vacuum pumps.

It is recommended for lubricating and cooling vacuum pumps handling air requiring this ISO viscosity grade. The product is compatible with standard seal and hose material and NOT recommended for pumps handling strong oxidizing and/or reactive vapours.

Benefits & Advantages

- Excellent protection against corrosion
- Excellent lubricity
- Oxidation stable

Performance Level

ISO VG-46/68/100: DIN 51524/2.
 ISO-VG 150/220: DIN 51517/3.
 Meets the specification of DIN 51506 VDL and ISO 6743-3A DAJ.

Typical Performance Data

Typical	Test Method	Value
ISO Viscosity Grade	ASTM D-2422	220
Density @ 20 °C, kg/l	ASTM D-1208	0.894
Kinematic viscosity @ 40 °C, cSt	ASTM D-445	216
Kinematic viscosity @ 100 °C, cSt	ASTM D-445	18.6
Viscosity Index	ASTM D-2270	96
Flash point C.O.C., °C	ASTM D-92	260
Pour point, °C	ASTM D-97	-18
Vapour pressure @ 20 °C, Pa	ASTM D-972	<0.5
TAN, mg KOH/gr	ASTM D-664	0.2

All performance data on this Technical Data Sheet are indicative only and can vary during production.